



ADVENT

Technologies, LLC

Honey Badger™ & UltraCell™ Fuel Cells

MADE IN THE USA

FUEL CELL ACCESSORIES

FLEXIBLE POWER DEVICE SPECIFIC CABLES

The UltraCell® fuel system is designed to deliver maximum power at a light weight for many mobile and other electronic devices, such as satellite communication terminals, rugged computers, and radios. Application-specific cables are a quick and easy way to ensure your UltraCell system works with your device.

2 BATT SLIM

7 Pin Glenair Circular Connector Tether to connect to 16.8 Volt to any of the UltraCell Fuel Cells.

- Tether length: 30 Inches
- Input: 16.8V, 80W
- Breakers: 2x 20A
- Voltage Output: 12 – 16.8V, 40A Max
- Battery: 2X Chargeable BB-2590
2x Trailer hitch connectors
- Part No. ACA0039-4



Military Device Adapter 14.4 Volt

6 pin Glenair to 7 pin Circular Connector Tether to connect to 14.4 volt military devices (see devices below).

- Tether length 3 feet (1m)
- Voltage output 14.4 V
- Part No AC781043



Military Distributed Smart Power Adapter 28.8 Volt

6 pin Glenair to 7 pin Circular Connector Tether to connect to 28.8 volt military devices (see devices below).

- Tether length 3 feet (1m)
- Voltage output 28.8 V
- Part No ACA0018



FUEL CELL ACCESSORIES

PRC-148 MBITR ADAPTER

Battery eliminator that makes the XX25 compatible with the AN/PRC-148 MBITR. Requires the AC781043 14.4 V Military Tether Adapter.

Tether length 6 feet (1.8m)
Voltage output 12 V
Part No AC741002



PRC-119F SINGARS ADAPTER

AN/PRC-119F (ASIP) Adapter allows the XX25 to interface with this radio through the P1 port. Requires the AC781043 14.4 V Military Tether Adaptor.

Tether length 6 feet (1.8m)
Voltage 14.4 V
NSN 5940-01-504-3218
Part No AC741007



PRC-117F/150 ADAPTER

DC-DC power adapter designed in conjunction with CERDEC. Battery box replacement that allows the XX25 to be used with the AN/PRC-117F and AN/PRC-150. Requires the AC781044 28.8 V Military Tether Adapter.

Tether length 6 feet (1.8m)
Voltage 24 V
NSN 5940-01-516-9787
Part No AC741003



BB-2590 FIELD MID-RATE CHARGER

Used to recharge the Military Battery BB-2590. Indicator shows when charge is complete.

Tether length 2 feet (0.6096 m)
Voltage output 19.5 V
Part No AC781048



FUEL CELL ACCESSORIES

CIGARETTE LIGHTER ADAPTER

Allows devices with cigarette lighter connectors to be powered using the UltraCell XX25.

Tether length 3 feet (1m)
Voltage output 14.4V
Part No AC781028



BA-5590/BB-2590 ELIMINATOR

Tether to connect XX25 to applications using the BA-5590/BB-2590 standard Military Radio. Requires the AC781034 28.8 V Military Tether Adapter.

Tether length 6 feet (1.8m)
Voltage output Dependent on Electric Fuel Tether used
Part No AC741001



Laptop Adapter Tethers

Connect DRS Laptop with 2.5 X 5.5mm plug to Fuel Cell .

Tether Length 3 feet (1m)
Voltage output 16.8 V
Part No AC781042

Connect Toughbook Laptop with 2.5 X 5.5mm plug to Fuel Cell .

Tether Length 3 feet (1m)
Voltage output 19 V
Part No AC781050



Development Blank End Cable

Used with our standard power connector and a cut blank end cable. This will allow a customer to supply their own device connection.

Tether length 3 feet (0.9 m)
Voltage output 16.8 V
Part No AC781051



ADVENT TECHNOLOGIES, LLC
5637 La Ribera Street Suite A Livermore CA 94550 USA
Tel: (925) 455-9400 Fax: (925) 455-7750
www.ultracell-llc.com sales@ultracell-llc.com