



GearUp!™

PN: SY011022 (w/options)

EXECUTIVE BATTERY OPTIMIZED POWER

AIRLINE COMPLIANT HIGH ENERGY UPS FOR EXECUTIVE INTERNATIONAL TRAVEL

OVFRVIFW

While on international travel, Executive Communications Teams (ECT) requires air travel compatible high energy UPS for backup comms power - up to 392Whr. Designed for the Road Warrior!

Take your UPS power system ANYWHERE. GearUp!™ meets airline carryon requirements for size & safety and fits the standard airlines personal baggage allowance.

Carryon luggage capable with IATA friendly batteries from Bren-Tronics.

Up to qty 4 MIL-STD BB-2557 batteries provide UPS power. 98Whr BT-70757BV, below IATA limits on carryon luggage for Li-Ion batteries

Use in parallel with mains for UPS operation uninterruptible! Run comms in vehicles or using solar power and maintain comms during brownouts or grid instability.





GearUp!™ Specifications



ELECTRICAL

INPUTS AC 88-265VAC 50-60hz

DC 10-36VDC [Cigarette lighter NATO Slave]

Foldable Solar Blankets

OUTPUTS AC 120VAC 60hz 250W

AC 240VAC = PN SY011022-2 15VDC 10A (battery bus)

28VDC 5A

135VDC 2.5A (high efficiency comms)

w/o 135VDC = PN SY011022-1

POE POE (48VDC, 350mA) & data jacks

IEEE 802.3af/at Type 1

USB 2X 5V 3.1A

CHARGE TIME 6hr

CONTAINER Powder Coated Aluminum, Ballistic Corners

Conformal Coated PCB

COLOR Army Tan

ENVIRONMENTAL REQUIREMENTS

OPERATING TEMP 32°F to +104°F

0°C to +40°C

STORAGE TEMP -40°F to +140°F

-40°C to +60°C

ACCESSORIES Part Number DC Input ACA0063 SATCOMMS ACA0064

28VDC - BB-2590, ACA0065
BA-5590 Receptacle High-Capacity Gear Up
BATTERY, Li ION, BB-2557, 99wh ACA0066

DUAL 15VDC/28VDC, PIGTAILS ACA0088

SOLAR PANEL W/MPPT, ACA0089

GEARUP! 60W





PART OPTIONS

| PN | Option | Batteries Qty 4 | Dimensions | Weight | Charge Time |
|--------------|----------------------------|----------------------------|---|--|-------------|
| SY011022 | BASE SYSTEM | MIL STD 2557 BT-70757BV | 15" x 9" x 2.9" 38cm x 23cm x 7.4cm | 11lb w/o Batteries 15.8lb w/4 Batteries | 6hr |
| SY011022-1 | W/O 135VDC | MIL STD 2557 BT-70757BV | 15" x 9" x 2.9" 38cm x 23cm x 7.4cm | 11lb w/o Batteries 15.8lb w/4 Batteries | 6hr |
| SY011022-1-1 | W/O 135VDC C14 AC INPUT | MIL STD 2557 BT-70757BV | 15" x 9" x 2.9" 38cm x 23cm x 7.4cm | 11lb w/o Batteries 15.8lb w/4 Batteries | 6hr |
| SY011022-2 | AC 240VAC | MIL STD 2557 BT-70757BV | 15" x 9" x 2.9" 38cm x 23cm x 7.4cm | 11lb w/o Batteries 15.8lb w/4 Batteries | 6hr |
| SY011022-3 | HIGH CAPACITY | MIL STD 2590 BT-70791BV | 15.5" x 9" x 4.1" 39.3cm x 23cm x 10.4cm | 11lb w/o Batteries 23.8lb w/4 Batteries | 9hr |

5637 La Ribera St. Suite A, Livermore, CA 94550 USA Tel: (925) 455-9400 Fax: (925) 455-7750 www.ultracell-llc.com sales@ultracell-llc.com